

graffiti away2

by NOOP'S COUP®

BENEFITS:

- Safer, faster, easier
- Super heavy duty
- Non-flammable
- Combustible
- User and environmentally friendly
- Less labor
- Multiple applications
- Industrial strength

PRODUCT DESCRIPTION: GRAFFITI AWAY 2 by NOOP'S COUP® is environmentally and user friendly. As a liquid, it removes graffiti from both porous and smooth surfaces. It clings to vertical surfaces and has a very low evaporation rate. Graffiti is removed from large areas because it can be applied with a paint brush or roller. Wash off with a power washer or hose with nozzle, and decrease your labor costs for spray applications.

RECOMMENDED APPLICATION: Test a small area first. Stir thoroughly before and during use. Apply remover - can be moved in any direction. Allow to work for 15-20 minutes. Use brass brush and scrub well. Always scrub away from yourself. Wash off with power washer. Always scrub away from yourself. If necessary, re-apply.

COST CONFIGURATION: Cost varies depending upon application and type of graffiti to be removed. Average coverage is 30 sq. ft. to 50 sq. ft. per gallon.

TECHNICAL SERVICES: Someone is normally available to answer questions regarding products in use. We have over 30 years of experience in paint removal. Our removers and cleaners REALLY WORK! All products are tested in our stripping plant, so we know what your problems are. Normal hours are 8:00 AM - 5:00 PM ET, Monday to Friday.

RECOMMENDED FOR USE ON MOST: Brick, concrete, wood, marble, glazed brick, terrazzo, porcelain tile, stainless steel, steel, cinder block, rocks, slate, stucco, ceramic tile, aluminum, and many more metals.

LIMITATIONS: The effectiveness of this product is decreased when temperatures are below freezing, or when it rains. DO NOT use this product on pre-painted surfaces unless you want them stripped. DO NOT use on asphalt, rubber, plastic tile, linoleum or carpet.



READ AND FOLLOW ALL INSTRUCTIONS & SAFETY PRECAUTIONS BEFORE USING THIS PRODUCT.

RECOMMENDED TEMPERATURES: 60°F - 100°F

Under 60°F: Use a heat lamp from 3 ft away to warm surface. Some very hard to remove industrial coatings will require additional time to work.

PERSONAL SAFETY: THIS PRODUCT DOES NOT BURN SKIN. But as with all chemicals, excessive use or overexposure may irritate or dry out skin. Use of long sleeved shirts, rubber gloves and safety goggles for your eyes are recommended.

EMERGENCY & FIRST AID:

Eyes: Flush thoroughly with water for 15 minutes. If irritation persists, seek medical attention.

Skin: Wash with soap and water.

Inhalation: Move to fresh air.

Clothing: Wash before re-use.

TECHNICAL DATA:

Color: Dark Green Liquid

Weight per Gallon: 8 lbs

Boiling Point: 310°F

Flash Point: 150°F

Vapor Pressure: (mmHg) @ 20°C <1

Solubility: (% in Water) Complete

VOC Vapor Pressure: (mmHg) @ 20°C = AP 0.3

SIZES AVAILABLE: 1 Quart, 1 Gallon, 5 Gallon

SEE MATERIAL SAFETY DATA SHEET FOR USE, PERSONAL SAFETY & DISPOSAL PROCEDURES.

Go to www.noopscoup.com for more information.

WARRANTY: NOOP'S COUP® Products are warranted against manufacturing defects and to perform as advertised and instructed on package. Use and application of the product must conform to product instructions. NOOP'S COUP® shall not, under any circumstances, be liable for any consequential or any other damages in connection with your use of this product. Liability for product shall not exceed replacement cost. (Product warranty & liability information is available from manufacturer.)



**Specialists in Removers
That Really Work!**

Manufactured by:
NOOP'S COUP®, LLC

Main Office:
108 Route 40
Newfield, NJ 08344
856-358-6001
Fax: 856-358-0206

Sales Office:
145 West Ruby Avenue
Palisades Park, NJ 07650
201-840-9300
Fax: 201-840-9301

Technical Information:
856-404-0338

www.noopscoup.com